

T820 DIY DMM

- Low cost
- Large LCD display
- Continuity
- Diode



Technical Specification

| | |
|-----------------|----------------------|
| DC Voltage | 200m,2,20,200,600V |
| AC Voltage | 200,600V |
| DC Current | 200μ,2m,20m,200m,10A |
| Resistance | 200,2K,20K,200K,20MΩ |
| Accuracy | |
| DC Voltage | ± 0.5% + 4 Digit |
| AC Voltage | ± 1.2% + 10 Digit |
| DC Current | ± 1.5% + 3 Digit |
| Resistance | ± 0.8% + 3 Digit |

Model Specification

| | |
|-----------------|------------------------|
| Dimensions (mm) | 145(L) x 85(W) x 30(H) |
| Power Source | 9V Battery |
| Weight | 170g |

**3 -1/2 Digits
1999 Counts**

T835 DIY DMM

- Low Cost
- Temperature
- Continuity
- Diode • Data hold



Technical Specification

| | |
|-----------------|----------------------|
| DC Voltage | 200,2,20,200,500V |
| AC Voltage | 200,500V |
| DC Current | 200m,2m,20m,200m,10A |
| Resistance | 200,2K,20K,200K,20MΩ |
| Temperature | -20°C to 1000°C |
| Accuracy | |
| DC Voltage | ± 0.5% + 2 Digit |
| AC Voltage | ± 1.2% + 10 Digit |
| DC Current | ± 1.0% + 2 Digit |
| Resistance | ± 0.8% + 2 Digit |
| Temperature | ± 1.0% + 3 Digit |

Model Specification

| | |
|-----------------|------------------------|
| Accessories | Temp Bead Probe |
| Dimensions (mm) | 150(L) x 73(W) x 35(H) |
| Power Source | 9V Battery |
| Weight | 156g |

NEW UPGRADED SPECIFICATION

**3 -1/2 Digits
1999 Counts**

T1300H Electronic DMM

- Low cost
- Backlit
- Diode
- Continuity
- Data hold



Technical Specification

| | |
|-----------------|--|
| DC Voltage | 200m,2,20,200,500V |
| AC Voltage | 200,500V |
| DC Current | 2m,20M,200M,10A |
| Resistance | 200,2K,20K,200K,200MΩ |
| Accuracy | |
| DC Voltage | ±0,5% + 2 Digit |
| AC Voltage | ±1,2% + 10 Digit |
| DC Current | 2m-200mA ±1%+2 Dig 200m-10A ±2,0% + 5 Dig |
| Resistance | ±1% + 5 Digit |
| Diode | ±1mV |

Model Specification

| | |
|-----------------|------------------------|
| Dimensions (mm) | 150(L) x 73(W) x 35(H) |
| Power Source | 9V Battery |
| Weight | 156g |

NEW UPGRADED SPECIFICATION

**3 -1/2 Digits
1999 Counts**

T235H Electrician's DMM

- Backlit
- Large display
- Temperature
- Data hold • Capacitance



Technical Specification

| | |
|-----------------|-------------------------|
| DC Voltage | 200mV,2mV,20,200,1000V |
| AC Voltage | 20v,200,750V |
| DC Current | 20mV,200mV,20A |
| AC Current | 200mV, 20A |
| Resistance | 200,20K,200K,20MΩ,200MΩ |
| Temperature | -20°C -1000°C |
| Capacitance | 20nf,2nf,2000μF |
| Accuracy | |
| DC Voltage | ± 0,5% + 3 Digit |
| AC Voltage | ± 0,8% + 5 Digit |
| DC Current | ± 1,5% + 5 Digit |
| AC Current | ± 1,5% + 5 Digit |
| Resistance | ± 0,8% + 3 Digit |
| Temperature | ± 0,8% + 4 Digit |
| Capacitance | ± 2,5% + 20 Digit |

Model Specification

| | |
|-----------------|------------------------|
| Accessories | Temp Bead Probe |
| Dimensions (mm) | 190(L) x 88(W) x 27(H) |
| Power Source | 9V Battery |
| Weight | 320g |

**3 -1/2 Digits
1999 Counts**

T48 Electronic DMM

- Backlit
- Temperature
- Capacitance
- Inductance
- Large display



Technical Specification

| | |
|-----------------|---------------------------|
| DC Voltage | 200m,2,20,200,1000V |
| AC Voltage | 200mV,2,20,200,750V |
| DC Current | 20μ,200μ,20m,200m,2A,20A |
| AC Current | 200M,2A,20A |
| Resistance | 200,2K,200K,2M,20M,2000MΩ |
| Frequency | 2K,200KHz |
| Inductance | 2m,20m,200m,2,20H |
| Temperature | -20 to 1000°C |
| Capacitance | 20n,200n,2μ,20μF,200μF |
| Accuracy | |
| DC Voltage | ±0,5% + 3 Digit |
| AC Voltage | ±0,8% + 5 Digit |
| DC Current | ± 0,8% + 3 Digit |
| AC Current | ± 1,0% + 5 Digit |
| Resistance | ± 0,8% + 3 Digit |
| Inductance | 200mH ± 2,5% + 20 Digit |
| Frequency | ±0,5% + 4 Digit |
| Temperature | ±1,0% + 4 Digit |
| Capacitance | 20nf-20μf ±2,5% +20 Digit |

Model Specification

| | |
|-----------------|------------------------|
| Accessories | Temp Bead Probe |
| Dimensions (mm) | 189(L) x 97(W) x 35(H) |
| Power Source | 9V Battery |
| Weight | 400g |

T3601 Electrician's DMM

- Backlit
- Large display
- Data hold
- Continuity



Technical Specification

| | |
|-----------------|-------------------------|
| DC Voltage | 200mV,2mV,20,200,1000V |
| AC Voltage | 20v,200,750V |
| DC Current | 20mV,200mV,20A |
| AC Current | 200mV, 20A |
| Resistance | 200,20K,200K,20MΩ,200MΩ |
| Capacitance | 20nf,2nf,200μF |
| Accuracy | |
| DC Voltage | ± 0,5% + 3 Digit |
| AC Voltage | ± 0,8% + 5 Digit |
| DC Current | ± 1,5% + 5 Digit |
| AC Current | ± 1,5% + 5 Digit |
| Resistance | ± 0,8% + 3 Digit |
| Capacitance | ± 2,5% + 20 Digit |

Model Specification

| | |
|-----------------|------------------------|
| Accessories | Temp Bead Probe |
| Dimensions (mm) | 155(L) x 90(W) x 48(H) |
| Power Source | 9V Battery |
| Weight | 270g |

**3 -1/2 Digits
1999 Counts**